



Vital Coat

V-200 Pro Protectant Coating
Technical Data Sheet (TDS)

Description

V-200 Pro Protectant Coating is a two-part Acrylic-Epoxy system that utilizes Vital Coat's unique acrylic resin. When mixed with Vital Coat Activator, this formulation will yield a water resistance shell within two hours of application which is a great advantage in case of inclement weather or other exposure to moisture. Once mixed, V-200 Pro Protectant Coating has a pot life of up to 72 hours and once applied will be dry to touch within 2 hours and reach a full cure in 24 hours at ambient temperatures. Even quicker with elevated temperatures. The ambient dried coating will have excellent resistance to solvents such as Methyl Ethyl Ketone (MEK), Acetone and Isopropyl Alcohol. Detergents and cleaners will not remove this coating. It also resists staining.

Primary Applications

V-100 Premium Sealer is a recommended for Interior or Exterior applications. It is extremely durable and will provide a protective coating to new or aged Wood, Concrete, Masonry, or Stone substrates. V-200 Pro Protectant Coating will not change the natural color of your substrate. It will dry clear and will inhibit the growth of mold and mildew.

Features/Benefits

- *Environmentally Friendly
- *Repels Oil Based Stains
- *Mold and Mildew Resistant
- *Corrosion Inhibitor
- *Water Resistant Finish
- *Protects Wood from Water Damage
- *Excellent Adhesion
- *Keeps Wood, Concrete and Masonry Looking Fresh and Clean

Technical Information

Property	Result
Solids +/- 2%	25.00%
Appearance	Clear to translucent solution
Odor	Mild
Application Temperature	50°F - 85°F
Pot Life after Mixing Part A with Part B	72 hours
VOC Content +/-2%	<25g/L
Dry to Touch	2 hours
Re-Coat Time	1 to 2 hours

Note*Higher temperatures will speed up activation time and decrease the pot life of our component products. For every additional 10 degrees in temperature, your coating's pot life will generally decrease by half. The ideal temperature for use is 80°F.

Packaging

This product is available in 1, and 5 gallon containers. Other quantities available upon request.

Coverage

The coverage rate will vary depending upon surface porosity and application method use. The typical range is approximately 200 to 300 sq. ft. per gallon per application and approximately 150 to 250 sq. ft. per gallon on rough surfaces.

Shelf Life

This product has a shelf life of up to one year in its original, sealed, unopened container prior to any activator or catalyst being added. If product appears to be hardened or separated contact Vital Coat before use.

Directions for Use

Surface Preparation: Concrete and masonry surfaces must be dry, structurally sound, free of loose or deteriorated concrete and free of dust, dirt, paint, efflorescence, oil and all other contaminants. For wood, remove and water damaged materials and clean surfaces free of any mildew, mold, soaps, detergents and any other contaminants. Do not apply if rain is in the forecast within 24 hours.

Mixing: Separate the **Vital Coat Activator** (Part B) from **V-200 Pro Protectant Coating** (Part A) and make sure you have all components required. Mix the entire contents of (Part A) into an appropriate size container for mixing. Add entire contents of (Part B) into the mixing container and mix using a spiral mixer of proper size for 5 to 7 minutes or longer if larger quantities until uniform. Let the mixed sealer rest until all foam and bubbles have dissipated (Approximately 5 min.). After resting, use product immediately. If mixing multiple containers, do not mix more than can be placed in 24 hours. Do not add water or mix with any other components not specified.

Placement: Prior to placement, always test the product on the surface to be treated in an inconspicuous area to ensure proper adherence and satisfactory appearance. Using an appropriate high pressure pump sprayer with a minimum flow rate of .25gal/min, apply a thin uniform layer of sealer in manageable coverage areas before moving to the next. Walk in dry areas only. Coating goes on with a clear to slight white color but will dry clear. Avoid excessive build up. To remove excessive build up, immediately back roll with light pressure using a medium nap roller after spraying. A second coat is recommended using the same application method. Wait a minimum of 1 hour between coats.

Curing: Do not touch treated surface during curing. Do not add water or allow water to come in contact while curing. Protect surface from debris coming in contact with surface while drying. Allow to dry completely for approximately 48 to 72 hours before allowing heavy traffic on the treated surface.

Clean-up

Immediately after use, Clean tools and equipment with soap and water before the material hardens. Dispose of containers in accordance with local and federal regulations.

Precautions/Limitations

Before handling, consult the Material Safety Data Sheet and Container Labels for physical and health hazard information.

Do not allow products to freeze in storage or during application.

It is not recommended to apply Vital Coat Sealers over other types of sealers.

Minimum surface and ambient temperature of 45°F (7°C) and rising at the time of application.

For optimum results, condition material to 65°F to 85°F (18°C to 29°C) at least 24 hours prior to use.

Caution! This product when cured may be slippery when wet.

Never mix with any form of liquid or solvent. Improper thinning may cause sealer to delaminate in a short time frame.

Test in an inconspicuous area prior to use.

Dried or cured sealer may be removed using diamond grinding method or solvent.

Rev. 15-Oct

Vital Coat is a NxTech Holdings LLC Brand. The information contained in this Technical Data Sheet (TDS) is furnished without warranty, expressed or implied. The information contained in this document is believed to be accurate and it is the best information available. NxTech Holdings LLC assumes no legal responsibility for the use or reliance upon this data and SPECIFICALLY DISCLAIMS ANY LIABILITY FOR CONSEQUENTIAL DAMAGES. NxTech Holdings, LLC makes no guarantees to the accuracy of suitability this information to specific applications. By receiving and using the products referenced herein, consumer assumes all risk and liability for all use and handling.

Vital Coat

2172 Arendell Way - Tallahassee, Fl. 32308

Phone: Toll Free 844-284-2858

email: info@VitalCoat.com

Visit us at www.vitalcoat.com